
DOYLE





Specifications

- Max Beam Size: 60' x 40"
- Minimum Drill Diameter: 1/4"
- Maximum Drill Diameter: 1-9/16"
- Drill Feed Rate: 2"-10" per Min
- Spindle Stroke: 13" Max
- Total Power: 20 H.P.
- Micromist Cooling System



For more information contact Doyle Structural Solutions

Call 570-369-5700 or email Machines@DoyleStructuralSolutions.com

Terms: 1/3 Cash with order; balance before shipment. Guarantee: Machines are sold with the understanding that, if not as represented, they may be returned, freight prepaid, within 30 days with full refund. This does not apply to machines sold "RS IS" Doyle Structural Solutions makes no warranty of merchantability or of fitness for purpose. Safety: This machine may or may not conform to the current 05HR Standards and other applicable safety regulations. It is the responsibility of the Buyer & User to provide proper safety equipment and devices to protect the operator from harm for any particular use or set-up, and to adequately safeguard and equip the machine to comply with all applicable safety standards. Indemnification: Buyer/User agrees to indemnify and hold harmless Seller from any and all claims and liabilities due to accidents caused by failure of Buyer/User, his employees or agents, to follow proper safety instructions or procedures when operating machine, or from failure of Buyer/User to comply with applicable safety standards. Applicable Law: The contract resulting from the acceptance of an order pursuant to this quotation shall be governed by the laws of the Commonwealth of Pennsylvania.